



<tr><td>1225</td></tr><tr><td>1240</td></tr><td>1250</td></tr><tr><td>1340</td></tr><tr><td>1450</td></tr><td>1510</td></tr><tr><td>1675</td></tr></table>	<tr><td>1225</td></tr><tr><td>1300</td></tr><tr><td>1400</td></tr><tr><td>1550</td></tr><tr><td>1735</td></tr></table>	<tr><td>1275</td></tr><tr><td>1385</td></tr><tr><td>1540</td></tr><tr><td>1735</td></tr><td></td></tr></table>	<tr><td>1260</td></tr><tr><td>1375</td></tr><tr><td>1515</td></tr><tr><td>1735</td></tr></table>
--	--	--	--

scope="" style="" dir="" id="" colspan="1" align="center" valign="top" lang=""><table bordercolorlight="#99b7d1" bordercolordark="#ffffff" align="center" bgcolor="#ffffff" border="1" cellpadding="2" cellspacing="0" width="80"><tr><td class="HEAD"><b>AVX 13</b></td></tr><tr align="center"><td class="HEAD" width="80"><b>La<br />mm</b></td></tr><tr><td>725</td></tr><tr><td>750</td></tr><tr><td>775</td></tr><tr><td>825</td></tr><tr><td>875</td></tr><tr><td>925</td></tr><tr><td>975</td></tr><tr><td>1000</td></tr><tr><td>1015</td></tr><tr><td>1025</td></tr><tr><td>1050</td></tr><tr><td>1075</td></tr><tr><td>1125</td></tr><tr><td>1175</td></tr></table>

id="" colspan="1" align="center" valign="top" lang=""><table bordercolorlight="#99b7d1" bordercolordark="#ffffff" align="center" bgcolor="#ffffff" border="1" cellpadding="2" cellspacing="0" width="80"><tr><td class="HEAD"><b>AVX 13</b></td></tr><tr align="center"><td class="HEAD" width="80"><b>La<br />mm</b></td></tr><tr><td>1200</td></tr><tr><td>1225</td></tr><tr><td>1275</td></tr><tr><td>1300</td></tr><tr><td>1310</td></tr><tr><td>1350</td></tr><tr><td>1375</td></tr><tr><td>1385</td></tr><tr><td>1450</td></tr><tr><td>1460</td></tr></table>

1525			1550
		1675	
	1750		

2500

AVP 13				
La				
865 *			1525 *	
	1750 *			

\*) Special version for KAROSA buses. Service free version with sections AVX10, AVX 13. Belts are resistant to temperatures from -45 °C to +80 °C. Increased resistance to mineral oils. Increased resistance to abrasion.

Example of marking: AVX 10 -1000La SF

AVX 10 - marking of section 1000 La - outside length

SF - marking of service free version